

WSA-24T

Order No. 25.7150

Wireless stereo transmitter, 2.4 GHz, for audio streaming.

- Matching the receiver WSA-24R
- Stereo/mono selector switch
- LED for indicating status and peak
- Interference-free operation due to FHSS technology (Frequency Hopping Spread Spectrum)
- Analogue line level input via 6.3 mm jacks L/R and 3-pole XLR L/R
- Metal housing
- Power is provided via enclosed plug-in power supply

Model	WSA-24T
Frequency range	20-20,000 Hz
THD	< 0.3%
Channel separation	≥ 90 dB
Operating range	> 30 m with clear view
Codecs	-
Power supply	via encl. power supply
Dimensions	130 x 54 x 130 mm
Weight	470 g
Connections	Inputs: 1 x 6.3 mm stereo jack L/R, analogue 1 x 3-pole XLR L/R, analogue
Other features	2.4 GHz, 25 channels, latency: 18 ms



WSA-24R

Order No. 25.7140

Wireless stereo receiver, 2.4 GHz, for audio streaming.

- Matching the transmitter WSA-24T
- Interference-free operation due to FHSS technology (Frequency Hopping Spread Spectrum)
- Analogue line level output via 6.3 mm jacks L/R
- Plastic housing
- Power is provided via enclosed plug-in power supply

Model	WSA-24R
Frequency range	20-20,000 Hz
THD	< 0.3%
Channel separation	≥ 90 dB
Codecs	-
Power supply	via encl. power supply
Dimensions	116 x 35 x 86 mm
Weight	118 g
Connections	Outputs: 1 x 6.3 mm stereo jack L/R, analogue
Other features	2.4 GHz, 25 channels, latency: 18 ms



FLY-16T

Order No. 25.9580



16-channel wireless PA audio transmitter, with UHF PLL technology.

- For wireless transmission of line audio signals in PA systems
- Frequency range: 823-832 MHz
- 16 pre-programmed channels, selectable
- Up to 8 intermodulation-free channels
- Low-latency transmission
- Indication for channel and battery status
- Supplied with USB cable

Model	FLY-16T
Description	16-channel wireless PA audio transmitter
Carrier frequency range	823-832 MHz
Audio frequency range	30-17,000 Hz
THD	0.3%
Transmitting power	10 mW
Operating range	approx. 90 m
Power supply transmitter	1 x 1.5 V batt. AA size, = 5 V/150 mA via micro USB jack
Dimensions transmitter	22 x 23 x 116 mm
Weight transmitter	54 g
Connections transmitter	3-pole XLR jack

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section „IMPORTANT INFORMATION“!



FLY-16R

Order No. 25.9570



16-channel wireless PA audio receiver, with UHF PLL technology.

- For wireless transmission of line audio signals in PA systems
- Frequency range: 823-832 MHz
- 16 pre-programmed channels, selectable
- Up to 8 intermodulation-free channels
- Low-latency transmission
- Multiple receivers FLY-16R can be operated via one transmitter FLY-16T
- Indication for channel and battery status
- Supplied with USB cable

Model	FLY-16R
Description	16-channel wireless PA audio receiver
Carrier frequency range	823-832 MHz
Audio frequency range	30-17,000 Hz
THD	0.3%
Power supply receiver	1 x 1.5 V batt. AA size, = 5 V/150 mA via micro USB jack
Dimensions receiver	22 x 23 x 102 mm
Weight receiver	25 g
Connections receiver	3-pole XLR plug

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section „IMPORTANT INFORMATION“!

