

## Tender text

### HPR-6

#### Efficient stereo headphone amplifier,

can also be used as a small power amplifier for 4-8  $\Omega$  speaker systems

- Robust metal housing
- Stereo RCA input
- 6.3 mm stereo output
- Volume control and balance control

#### Specifications:

|                       |   |
|-----------------------|---|
| Description           | stereo headphone amplifier  |
| Frequency range       | 19-40,000 Hz  |
| Input signal          | 110 mV-4 V  |
| Output signal         | 2 x 525 mW/2 x 1,500 mW/4 $\Omega$ ,<br>2 x 330 mW/2 x 750 mW/8 $\Omega$ ,<br>2 x 114 mW/2 x 200 mW/32 $\Omega$ |
| S/N ratio             | 69 dB   |
| THD                   | 1%  |
| Admiss. ambient temp. | 0-40 °C   |
| Power supply          | via<br>encl. plug-in power supply   |
| Dimensions            | 120 x 68 x 36 mm  |
| Weight                | 288 g   |
| Inputs                | 2 x RCA L/R   |
| Outputs               | 1 x 6.3 mm jack   |

Brand: IMG STAGELINE

Type: HPR-6

Quantity: 1

Packing dimensions (W x H x L): 0.05 x 0.165 x 0.165 m

Gross weight: 0.372 kg

Net weight: 0.288 kg

Item weight (w/o accessories): 0.288 kg