

TXS-606DT

Order No. 25.7310

Wireless desktop microphone with integrated multifrequency transmitter, with UHF PLL technology.

- Electret microphone cartridge, cardioid polar pattern
- 350 mm gooseneck, removable
- 1,000 select. UHF frequencies (672.000-696.975 MHz), can be synchronised with receivers TXS-606, TXS-626, TXS-646 or TXS-686 via ACT function
- Adjustable sensitivity
- Switchable transm. power (high: 25 mW/low: 2.5 mW)
- LCD for indicating group/channel, audio level and battery status

Model	TXS-606DT
Polar pattern	cardioid
System	electret
Carrier frequency range	672.000-696.975 MHz
Transmitting power	25 mW/2.5 mW
Power supply	2 x 1.5 V batt. AA size
Operating time	> 8 h
Audio frequency range	30-18,000 Hz
Dimensions	120 x 65 x 178 mm (w/o gooseneck)
Weight	600 g



TXS-606HSE

Order No. 25.4690

Multifrequency pocket transmitter, with UHF PLL technology.

- 1,000 select. UHF frequencies (672.000-696.975 MHz), can be synchronised with receivers TXS-606, TXS-626 or TXS-646 via ACT function
- Continuously adjustable sensitivity
- LCD for indicating group/channel, audio level and battery status
- Suitable for combination with headband/earband microphones and tie clip microphones with 3-pole mini XLR connector

Model	TXS-606HSE
Carrier frequency range	672.000-696.975 MHz
Audio frequency range	30-18,000 Hz
Operating time	> 8 h
Transmitting power	10 mW
Power supply transmitter	2 x 1.5 V batt. AA size
Dimensions transmitter	61 x 106 x 27 mm
Weight transmitter	96 g
Connections transmitter	1 x 3-pole mini XLR



TXS-606HT

Order No. 25.3540

Hand-held microphone with integrated multifrequency transmitter, with UHF PLL technology.

- Dynamic microphone cartridge, cardioid polar pattern
- 1,000 select. UHF frequencies (672.000-696.975 MHz), can be synchronised with receivers TXS-606, TXS-626 or TXS-646 via ACT function
- Adjustable sensitivity
- Switchable transmitting power (high: 25 mW/low: 2.5 mW)
- LCD for indicating group/channel, audio level and battery status

Model	TXS-606HT
Polar pattern	cardioid
System	dynamic
Carrier frequency range	672.000-696.975 MHz
Transmitting power	25 mW/2.5 mW
Power supply	2 x 1.5 V batt. AA size
Operating time	> 8 h
Audio frequency range	30-18,000 Hz
Dimensions	Ø 51 mm x 265 mm
Weight	312 g



TXS-606LT

Order No. 25.3550

Multifrequency tie clip microphone transmitter, with UHF PLL technology.

- 1,000 select. UHF frequencies (672.000-696.975 MHz), can be synchronised with receivers TXS-606, TXS-626 or TXS-646 via ACT function
- Continuously adjustable sensitivity
- LCD for indicating group/channel, audio level and battery status
- Tie clip microphone with latchable 3.5 mm plug

Model	TXS-606LT
Carrier frequency range	672.000-696.975 MHz
Audio frequency range	30-18,000 Hz
Operating time	> 8 h
Transmitting power	10 mW
Power supply transmitter	2 x 1.5 V batt. AA size
Dimensions transmitter	61 x 106 x 27 mm
Weight transmitter	125 g
Connections transmitter	1 x 3.5 mm jack

