

Microphones

Wireless Transmission

TXS-727

Order No. 25.7530



2-channel multifrequency receiver unit, with UHF PLL technology.

- 100 selectable UHF frequencies (667.000-691.750 MHz) for each channel
- SYNC function
- Diversity system with removable antennas
- Volume and squelch controls adjustable for each channel
- Pilot tone squelch

Model	TXS-727
Carrier frequency range	667.000-691.750 MHz
Audio frequency range	80-18,000 Hz
THD	< 0.5%
Dynamic range	100 dB
RF S/N ratio	105 dB
Audio signal receiver	100 mV/600 Ω (jack) 20-30 mV/600 Ω (XLR, bal.)
Power supply receiver	via encl. plug-in power supply
Dimensions receiver	482 x 50 x 255 mm
Weight receiver	1.65 kg
Connections receiver	2 x XLR, bal., 1 x 6.3 mm jack, unbal.



TXS-707

Order No. 25.7540



Multifrequency receiver unit, with UHF PLL technology.

- 100 selectable UHF frequencies (667.000-691.750 MHz)
- SYNC function
- True diversity system with removable antennas
- Volume and squelch controls
- Pilot tone squelch

Model	TXS-707
Carrier frequency range	667.000-691.750 MHz
Audio frequency range	80-18,000 Hz
THD	< 0.5%
Dynamic range	100 dB
RF S/N ratio	105 dB
Audio signal receiver	100 mV/600 Ω (jack) 20-30 mV/600 Ω (XLR, bal.)
Power supply receiver	via encl. plug-in power supply
Dimensions receiver	210 x 50 x 215 mm
Weight receiver	970 g
Connections receiver	1 x XLR, bal., 1 x 6.3 mm jack, unbal.



TXS-707HT

Order No. 25.7560

Hand-held microphone with integrated multifrequency transmitter, with UHF PLL technology.

- Dynamic microphone cartridge, cardioid polar pattern
- 100 selectable UHF frequencies (667.000-691.750 MHz)
- Switchable transmitting power (high: 30 mW/low: 2.5 mW)
- Mute function
- Operating range: 120 m (free field)

Model	TXS-707HT
Polar pattern	cardioid
System	dynamic
Carrier frequency range	667.000-691.750 MHz
Transmitting power	2.5 mW/30 mW
Power supply	2 x 1.5 V batt. AA size
Operating time	> 15 h
Audio frequency range	30-18,000 Hz
Dimensions	Ø 55 mm x 257 mm
Weight	332 g



TXS-707HSE

Order No. 25.7550

Multifrequency pocket transmitter, with UHF PLL technology.

- 100 selectable UHF frequencies (667.000-691.750 MHz)
- Continuously adjustable sensitivity
- Gain control
- Mute function
- LCD for indicating channel and battery status
- Operating range: 90 m (free field)

Model	TXS-707HSE
Carrier frequency range	667.000-691.750 MHz
Audio frequency range	30-18,000 Hz
Operating time	> 15 h
Transmitting power	10 mW
Power supply transmitter	2 x 1.5 V batt. AA size
Dimensions transmitter	62 x 105 x 26 mm
Weight transmitter	77 g
Connections transmitter	1 x 3-pole mini XLR



TXS-707LT

Order No. 25.7570

Multifrequency tie clip microphone transmitter, with UHF PLL technology.

- 100 selectable UHF frequencies (667.000-691.750 MHz)
- Continuously adjustable sensitivity
- Gain control
- Mute function
- LCD for indicating channel and battery status
- Operating range: 90 m (free field)

Model	TXS-707LT
Carrier frequency range	667.000-691.750 MHz
Audio frequency range	30-18,000 Hz
Operating time	> 15 h
Transmitting power	10 mW
Power supply transmitter	2 x 1.5 V batt. AA size
Dimensions transmitter	62 x 105 x 26 mm
Weight transmitter	77 g
Connections transmitter	1 x 3.5 mm jack

