

Microphones

Large Diaphragm Microphones

ECMS-90

Order No. 23.6970



Large diaphragm condenser microphone, for professional studio applications.

- 2.8 cm (1.1") extra thin gold-plated diaphragm
- Low cut switch
- 10 dB attenuation, switchable
- 48 V phantom power
- Supplied with vibration absorbing support (spider) with 16 mm (5/8") thread, microphone windshield and leather bag
- Supplied in a foam-padded case

Model	ECMS-90
Polar pattern	cardioid
System	condenser
Audio frequency range	20-20,000 Hz
Nominal impedance	200 Ω
Sensitivity	20 mV/Pa
S/N ratio	78 dB
Max. sound pressure	135 dB
Power supply	= 48 V, phantom power
Housing material	metal
Dimensions	Ø 50 mm x 185 mm
Weight	430 g
Connection	XLR, bal.



ECMS-70

Order No. 23.6960



Large diaphragm condenser microphone, for professional studio applications.

- 2.5 cm (1") extra thin gold-plated diaphragm
- 48 V phantom power
- Supplied with vibration absorbing support (spider) with 16 mm (5/8") thread and leather bag

Model	ECMS-70
Polar pattern	cardioid
System	condenser
Audio frequency range	20-20,000 Hz
Nominal impedance	150 Ω
Sensitivity	20 mV/Pa
S/N ratio	78 dB
Max. sound pressure	132 dB
Power supply	= 48 V, phantom power
Housing material	metal
Dimensions	Ø 50 mm x 185 mm
Weight	310 g
Connection	XLR, bal.

