

DM-1100

Order No. 0233290

Dynamic microphone, for speech and vocals.

- Cardioid polar pattern
- Supplied with cable
- Supplied w/o microphone holder. Matching microphone holder (e.g. MH-202) is available at option

Model	DM-1100
Polar pattern	cardioid
System	dynamic
Audio frequency range	50-16,000 Hz
Nominal impedance	500 Ω
Sensitivity	2.5 mV/Pa
Max. sound pressure	145 dB
Housing material	metal
Dimensions	Ø 54 mm x 175 mm
Weight	250 g
Cable	5 m, low-noise, 6.3 mm plug
Connection	XLR, bal.



DM-1500

Order No. 0236750

Dynamic microphone, for general applications.

- Cardioid polar pattern
- High-gloss aluminium version, black chromium-plated
- On/off switch

Model	DM-1500
Polar pattern	cardioid
System	dynamic
Audio frequency range	80-12,000 Hz
Nominal impedance	600 Ω
Sensitivity	1.8 mV/Pa
Max. sound pressure	140 dB
Housing material	aluminium
Dimensions	Ø 45 mm x 165 mm
Weight	274 g
Cable	3 m, low-noise, 6.3 mm plug
Connection	XLR, bal.



DM-3SET

Order No. 0234020

Dynamic vocal microphone set

Set of 3 vocal microphones, ideally suited for recordings and live performances. The frequency response has been especially optimised for vocal applications which makes the DM-3SET a reliable tool for any vocalist.

- Wide transmission range
- Very low acoustic feedback
- Integrated windshield/pop noise head
- Suitable for on-the-road applications due to diecast body and steel basket
- Supplied accessories: robust hard-sided case, 3 x stand clamp 16 mm (5/8")

Model	DM-3SET
Polar pattern	cardioid
System	dynamic
Audio frequency range	50-15,000 Hz
Nominal impedance	500 Ω
Sensitivity	2 mV/Pa
Max. sound pressure	120 dB
Housing material	diecast zinc
Dimensions	Ø 53 mm x 180 mm
Weight	285 g
Connection	XLR, bal.

