

## TXS-2402SET

Order No. 0254090

### Digital wireless 2-channel PLL microphone system, 2.4 GHz

- 2 microphone transmitters, 1 receiver, 1 plug-in power supply
- High resistance to interference due to digital transmission
- 2 systems can be used in parallel
- 16 frequencies for each channel can be selected at the transmitter
- Wireless auto-configuration of the receiver
- Volume control for each channel
- 6.3 mm output for mixed signal

Licence-free in the EU.



Model	TXS-2402SET
Carrier frequency range	2,404-2,476 MHz
Audio frequency range	80-12,000 Hz
THD	< 0.1%
Dynamic range	87 dB
Admiss. ambient temp.	0-40 °C
Transmitting power	10 mW
Operating range	approx. 30 m (free field) approx. 20 m (indoors)
Power supply transmitter	2 x 1.5 V batt. AA size
Dimensions transmitter	Ø 54 mm x 225 mm
Weight transmitter	120 g
Audio signal receiver	100 mV/600 Ω
Power supply receiver	via encl. plug-in power supply
Dimensions receiver	220 x 45 x 150 mm
Weight receiver	550 g
Connections receiver	1 x 6.3 mm jack, unbal.

## TXS-2401SX

Order No. 0254680

### Digital wireless pocket transmitter, 2.4 GHz, matching the 2-channel PLL microphone system TXS-2402SET.

- High resistance to interference due to digital transmission
- 16 selectable frequencies (2,404-2,476 MHz)
- Volume control
- Power LED
- Belt clip
- Headband microphone and tie clip microphone, each with latchable 3.5 mm plug
- Power supply via 2 x 1.5 V battery AA size (not supplied)

Licence-free in the EU.



Model	TXS-2401SX
Carrier frequency range	2,404-2,476 MHz
Audio frequency range	80-12,000 Hz
Operating time	> 20 h
Admiss. ambient temp.	0-40 °C
Transmitting power	10 mW
Power supply transmitter	2 x 1.5 V batt. AA size
Dimensions transmitter	62 x 90 x 28 mm
Weight transmitter	105 g
Connections transmitter	1 x 3.5 mm jack

There are restrictions or requirements in the EU!  
Please read the notes on wireless systems in the section "IMPORTANT INFORMATION"!