



DELTA-160

Order No. 0203190



16-channel digital audio mixer

- 12 mono input channels (comb. inputs XLR/6.3 mm jack)
- 2 stereo input channels
- 1 S/PDIF input
- 1 USB audio channel
- USB recording (stereo master) and playback with 192 kHz/24 bits max.
- Integrated DSP (2 x reverb, 2 x modulation, 2 x delay, 2 x 31-band graphic equalizer)
- 8 XLR outputs
- 1 monitor output (6.3 mm jack)
- 1 AES/EBU output
- 1 S/PDIF output
- Can be remote-controlled via app (iOS)
- +48 V phantom power, can be activated as required for each mono input channel
- 1 adjustable headphone output
- 17.8 cm (7") colour LCD touch screen for display and settings
- Supplied with power supply



Model	DELTA-160
Mic input	0.4 mV/3 mV, bal. (comb. jack)
Line input	8 mV, bal. (stereo)
Master output	700 mV, bal. (XLR)
Monitor output	700 mV, bal. (6.3 mm jack)
Headphones	> 8 Ω
Frequency range	20-20,000 Hz
THD	< 0.01%
Crosstalk	> 69 dB
Equalizer bass	DSP (4-band equalizer)
Equalizer midrange	DSP (4-band equalizer)
Equalizer treble	DSP (4-band equalizer)
Power supply	vie encl. power supply
Dimensions	335 x 140 x 410 mm
Weight	5.55 kg

RM/DELTA-160

Order No. 0203230



482 mm mounting bracket set

- For rack installation of 16-channel digital audio mixer DELTA-160
- 2 mounting brackets
- Black lacquered metal version

