



PMX-122FX

Order No. 0202870



Powered mixer, 2 x 475 W, 4 Ω, with digital amplifier and 2 DSP effect units.

- Audio mixer and digital amplifier in a metal housing
- 12 mono input channels, each with gain control, 3-way equalizer with semiparametric midrange, low cut and pan pot
- 2 stereo input channels, each with gain control, 4-way equalizer and balance control
- 2 x DSP, each with 100 different effects, e.g. reverb, hall, echo and multi-effects
- Integrated, adjustable compressor/limiter
- Adjustable stereo aux return inputs and FX send outputs

- Control room function
- Inserts for mono input channels
- Tape record/play connections
- +48 V phantom power, can be activated as required for each input channel group
- Adjustable headphone output
- 7-band graphic equalizer
- Stereo LED level display
- Connection for gooseneck light GNL-304, GNL-305 or GNL-314

Model	PMX-122FX
Mic input	0.5 mV, bal., 12 x 3-pole XLR
Line input	8 mV, bal. (stereo), 2 x 6.3 mm jack L/R 2 mV, bal. (mono), 12 x 6.3 mm jack
Tape (play)	60 mV, 1 x RCA L/R
Aux input	60 mV, bal., 2 x 6.3 mm jack L/R
Insert input	80 mV, 12 x 6.3 mm jack
Master output	1.5 V, bal., 1 x 3-pole XLR L/R
Aux output	10 V, 4 x 6.3 mm jack
Control room	10 V, stereo, 1 x 6.3 mm jack
Tape (rec)	680 mV, 1 x RCA L/R
Headphones	≥ 8 Ω, 1 x 6.3 mm jack
Frequency range	20-20,000 Hz
THD	< 0.04%
S/N ratio	89 dB
Crosstalk	-63 dB
Equalizer bass	±15 dB/80 Hz
Equalizer midrange	±15 dB/100-8,000 Hz (mono channels) ±15 dB/500 Hz (stereo channels) ±15 dB/3 kHz (stereo channels)
Equalizer treble	±15 dB/12 kHz
Power supply	~ 230 V/50 Hz/1,250 VA
Dimensions	545 x 145 x 465 mm
Weight	10.5 kg



PMX-164

Order No. 0203150



Powered mixer, 70 W, 4 Ω

- Audio mixer and audio amplifier built into a wooden housing with black felt covering
- 5 mono input channels, each with gain control, 2-way tone control and effect control

- 1 mono input channel (stereo input) with gain control, 2-way tone control and effect control
- Integrated Bluetooth receiver
- Integrated MP3 player with USB port, SD card slot and illuminated LCD

Model	PMX-164
Mic input	1.5 mV, bal., 6 x 3-pole XLR
Line input	15 mV, bal., 5 x 6.3 mm jack, 85 mV, 1 x RCA L/R, 550 mV, 1 x 6.3 mm jack
Tape (play)	200 mV, 1 x RCA L/R
Monitor output	7.5 V, 1 x 6.3 mm jack (sub out)
Tape (rec)	550 mV, 1 x RCA L/R
Frequency range	20-20,000 Hz
THD	0.1%
S/N ratio	> 65 dBA
Equalizer bass	± 15 dB/80 Hz
Equalizer treble	± 15 dB/10 kHz
Power supply	~ 230 V/50 Hz/210 VA
Dimensions	400 x 220 x 230 mm
Weight	7 kg

- Adjustable digital delay
- Tape record and CD/tape play connections
- 5-band graphic equalizer
- Low-pass filter: 200 Hz, 6 dB/oct.
- Sub-out output for connecting an active subwoofer