

PAK-312M/SW

Order No. 0257170



Universal active PA speaker system with DSP, 500 W

- Compact 12/2 full range bass-reflex system
- 30 cm (12") coaxial speaker system with 25 mm (1", 44 mm voice coil) horn tweeter
- DSP-controlled 2-channel amplifier system, bass: class D, tweeter: analogue
- 3 selectable presets: music, flat and low cut (120 Hz)
- High-quality cabinet made of multiplex wood with protective metal grille
- Integrated stand sleeve for multi-purpose positioning

Model	PAK-312M/SW
Power rating (RMS)	DSP-controlled, 370 W (300+70) bass: 300 W tweeter: 70 W
Frequency range	50-20,000 Hz
Input signal	500 mV/20 kΩ (line, bal), 7 mV/1 kΩ (mic, bal.)
Sensitivity	98 dB/W/m
Power supply	~ 230 V/50 Hz/510 VA
Dimensions	480 x 380 x 500 mm
Weight	19 kg
Inputs	2 x comb. XLR/6.3 mm (line/mic A, line B)
Outputs	2 x XLR, par. out, 1 x XLR MIX out



PAB-312M/SW

Order No. 0256020



High-power PA stage monitor, 500 W, 8 Ω

- High-performance 12/2 full range bass-reflex system
- 30 cm (12") coaxial speaker system with 25 mm (1", 44 mm voice coil) horn tweeter
- Consistent radiation pattern due to coaxial system
- Protective circuit for the tweeter
- High-quality cabinet made of MDF wood with robust protective metal grille
- Integrated stand sleeve and M10 threaded inserts

Model	PAB-312M/SW
Total power rating	500 W
Power rating (RMS)	250 W
Impedance	8 Ω
Frequency range	65-20,000 Hz
Sensitivity	98 dB/W/m
Dimensions	480 x 380 x 500 mm
Weight	18 kg
Inputs	1 x NEUTRIK SPEAKON
Outputs	1 x NEUTRIK SPEAKON, par. out



PAK-308M/SW

Order No. 0255110



Universal active PA speaker system with DSP, 500 W

- Compact 8/2 full range bass-reflex system
- 20 cm (8") coaxial speaker system with 25 mm (1", 44 mm voice coil) horn tweeter
- DSP-controlled 2-channel amplifier system, bass: class D, tweeter: analogue
- 3 selectable presets: music, flat and low cut
- High-quality cabinet made of multiplex wood with protective metal grille
- Supplied with mounting bracket and integrated stand sleeve

Model	PAK-308M/SW
Power rating (RMS)	DSP-controlled, 370 W (300+70) bass: 300 W tweeter: 70 W
Frequency range	60-20,000 Hz
Input signal	775 mV/20 kΩ (line, bal.), 10 mV/20 kΩ (mic, bal.)
Sensitivity	97 dB/W/m
Power supply	~ 230 V/50 Hz/350 VA
Dimensions	340 x 303 x 379 mm
Weight	10.75 kg
Inputs	2 x comb. XLR/6.3 mm (line/mic A, line B)
Outputs	2 x XLR, par. out, 1 x XLR MIX out



PAB-308M/SW

Order No. 0255100



Universal PA speaker system, 300 W, 8 Ω

- Compact 8/2 full range bass-reflex system
- 20 cm (8") coaxial speaker system with 25 mm (1", 44 mm voice coil) horn tweeter
- High-quality cabinet made of birch plywood with metal protective grille
- Multi-purpose positioning and installation options, especially as a floor monitor
- Supplied with mounting bracket and integrated stand sleeve
- NEUTRIK SPEAKON terminal

Model	PAB-308M/SW
Total power rating	300 W
Power rating (RMS)	150 W
Impedance	8 Ω
Frequency range	80-20,000 Hz
Sensitivity	96 dB/W/m
Dimensions	340 x 303 x 379 mm
Weight	10 kg
Inputs	1 x NEUTRIK SPEAKON
Outputs	1 x NEUTRIK SPEAKON, par. out

