

Components

Stage and Audio Accessories

MD-4600

Order No. 22.0680

Stereo headphones

- For general applications
- Closed system
- Padded ear cushions
- 2 m cable with single-sided cable inlet
- Gold-plated 3.5 mm plug with 6.3 mm adapter

Model	MD-4600
Headphone driver	ferrite
Type of transducer	dynamic
Max. input power	30 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	105 dB/mW
Cable	2 m, single-sided cable inlet
Plug	3.5 mm plug
Adapter	6.3 mm plug
Weight w/o cable	200 g



MD-390

Order No. 22.0100

Stereo headphones

- For general applications
- Closed system
- Padded ear cushions and headband
- 1.5 m cable with single-sided cable inlet
- Gold-plated 3.5 mm plug with 6.3 mm adapter

Model	MD-390
Headphone driver	neodymium, Ø 40 mm
Type of transducer	dynamic
Max. input power	100 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	32 Ω
Cable	1.5 m, single-sided cable inlet
Plug	3.5 mm plug, gold-plated
Adapter	6.3 mm plug, gold-plated
Weight w/o cable	160 g



MDH-6300

Order No. 22.1090

Mono hand-held DJ headphone

- Powerful neodymium magnet driver Ø 50 mm
- Closed system
- Movable earpiece
- Padded ear cushion
- Ergonomic padded handle
- Removable helix connection cable (1.3-2.8 m) with latchable XLR inline jack and right-angle 6.3 mm stereo plug
- Supplied with transport bag

Model	MDH-6300
Headphone driver	neodymium, Ø 50 mm
Type of transducer	dynamic
Max. input power	3,500 mW
Transmission range, headphones	10-22,000 Hz
Nominal impedance, headphones	46 Ω
Headphone sensitivity	96 dB/mW
Cable	1.3-2.8 m
Plug	6.3 mm plug
Weight w/o cable	152 g

