

TXS-2402SET

Order No. 0254090

Digital wireless 2-channel PLL microphone system, 2.4 GHz

- 2 microphone transmitters, 1 receiver, 1 plug-in power supply
- High resistance to interference due to digital transmission
- 2 systems can be used in parallel
- 16 frequencies for each channel can be selected at the transmitter
- Wireless auto-configuration of the receiver
- Volume control for each channel
- 6.3 mm output for mixed signal

Licence-free in the EU.

Model	TXS-2402SET
Carrier frequency range	2,404-2,476 MHz
Audio frequency range	80-12,000 Hz
THD	< 0.1%
Dynamic range	87 dB
Admiss. ambient temp.	0-40 °C
Transmitting power	10 mW
Operating range	approx. 30 m (free field) approx. 20 m (indoors)
Power supply transmitter	2 x 1.5 V batt. AA size
Dimensions transmitter	Ø 54 mm x 225 mm
Weight transmitter	120 g
Audio signal receiver	100 mV/600 Ω
Power supply receiver	via encl. plug-in power supply
Dimensions receiver	220 x 45 x 150 mm
Weight receiver	550 g
Connections receiver	1 x 6.3 mm jack, unbal.



TXS-2401SX

Order No. 0254680

Digital wireless pocket transmitter, 2.4 GHz, matching the 2-channel PLL microphone system TXS-2402SET.

- High resistance to interference due to digital transmission
- 16 selectable frequencies (2,404-2,476 MHz)
- Volume control
- Power LED
- Belt clip
- Headband microphone and tie clip microphone, each with latchable 3.5 mm plug
- Power supply via 2 x 1.5 V battery AA size (not supplied)

Licence-free in the EU.

Model	TXS-2401SX
Carrier frequency range	2,404-2,476 MHz
Audio frequency range	80-12,000 Hz
Operating time	> 20 h
Admiss. ambient temp.	0-40 °C
Transmitting power	10 mW
Power supply transmitter	2 x 1.5 V batt. AA size
Dimensions transmitter	62 x 90 x 28 mm
Weight transmitter	105 g
Connections transmitter	1 x 3.5 mm jack



TXS-812SET

Order No. 0252600



Wireless 2-channel microphone system

- 2 microphone transmitters, 1 receiver, 1 plug-in power supply
- Two-channel UHF version (non-diversity) with channel mixing function which can additionally be selected
- Volume and squelch controls for each channel
- Each channel with LEDs for indicating RF signal and audio signal

Licence-free in the EU.

Model	TXS-812SET
Carrier frequency range	863.80 MHz, 864.20 MHz
Audio frequency range	40-15,000 Hz
THD	< 0.5%
Dynamic range	> 90 dB
RF S/N ratio	> 80 dB
Admiss. ambient temp.	0-40 °C
Transmitting power	< 10 mW
Operating range	approx. 30 m
Power supply transmitter	2 x 1.5 V batt. AA size (not supplied)
Dimensions transmitter	Ø 52 mm x 260 mm
Weight transmitter	240 g
Audio signal receiver	0-200 mV/10 kΩ (jack) 0-400 mV/10 kΩ (XLR, bal.)
Power supply receiver	via encl. plug-in power supply
Dimensions receiver	210 x 46 x 190 mm
Weight receiver	560 g
Connections receiver	2 x XLR, bal. 1 x 6.3 mm jack, unbal.

