

Highlights

FLAT-M8

Order No. 1000766



Active PA stage monitor speaker system, 300 W

- Flat and very compact full range system
- Fitted with a 20 cm (8") coaxial speaker with horn tweeter
- Class D amplifier system
- Sound pressure at nominal power: 121 dB
- Indication of protect, limiter, signal and power-on
- Volume control and 3-way tone control (bass, midrange and treble)
- Balanced line/mic input and feed-through output
- Unbalanced line input RCA L/R or 6.3 mm jack
- Switchable automatic power-off
- High-quality plywood cabinet with protective metal grille
- M10 threaded insert for stand adapter or mounting device

| Model | FLAT-M8 |
|--------------------|---|
| Total output power | 300 W |
| Power rating (RMS) | 100 W |
| Frequency range | 70-21,000 Hz |
| THD | - |
| S/N ratio | - |
| Input signal | 180 mV/5,6 kΩ (line, bal.), 180 mV/5,6 kΩ (aux, RCA) 1.5 mV/1.2 kΩ (mic, bal), 70 mV/4 kΩ (aux, 6.3 mm jack, asym.) |
| SPL | 99 dB/W/m |
| Mounting device | 1 x M10 threaded insert |
| Power supply | ~ 230 V/50 Hz/100 VA |
| Dimensions | 375 x 185 x 330 mm |
| Weight | 7.3 kg |
| Inputs | 1 x comb. XLR/6.3 mm (mic), 1 x comb. XLR/6.3 mm (line), 1 x RCA L/R, 1 x 6.3 mm stereo jack |
| Outputs | 1 x XLR direct out |



FLAT-M8BAG

Order No. 1000771

Transport and protective bag

- Suitable for active PA stage monitor speaker system FLAT-M8
- Black, partly padded nylon version with zip fastener
- Carrying handle, rubber feet and lateral cable bag

