

## MD-306

Order No. 0221070

### Stereo headphones

- Extra lightweight version
- Turnable earpieces
- Padded ear cushions
- 1.2 m cable with single-sided cable inlet and 3.5 mm plug

Model	MD-306
Headphone driver	neodymium, Ø 30 mm
Type of transducer	dynamic
Max. input power	50 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	110 dB/mW
Cable	1.2 m, single-sided cable inlet
Plug	3.5 mm plug
Weight w/o cable	50 g



## MD-480

Order No. 0221190

### Stereo headphones

- For general applications
- Compact design
- Closed system
- Padded ear cushions and headband
- 1.2 m cable with single-sided cable inlet
- 3.5 mm plug with 6.3 mm adapter

Model	MD-480
Headphone driver	neodymium, Ø 38 mm
Type of transducer	dynamic
Max. input power	200 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	95 dB/mW
Cable	1-2 m, single-sided cable inlet
Plug	3.5 mm plug
Adapter	6.3 mm plug
Weight w/o cable	150 g



## MD-39

Order No. 0220070

### Stereo headphones

- Well-balanced sound
- Universal headphones
- Extra lightweight version
- 1.2 m cable with 3.5 mm stereo plug

Model	MD-39
Headphone driver	ferrite
Type of transducer	dynamic
Max. input power	100 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	32 Ω
Cable	1.1 m
Plug	3.5 mm plug
Weight w/o cable	28 g



## MD-22

Order No. 0221270

### Stereo headphones

- Ideally suited for guided tours, coaches, hospitals or hotels
- 1.5 m cable with 3.5 mm stereo plug
- Individually packed in a plastic bag

Model	MD-22
Headphone driver	ferrite, Ø 27 mm
Type of transducer	dynamic
Max. input power	20 mW
Transmission range, headphones	100-18,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	102 dB/mW
Cable	1.5 m
Plug	3.5 mm plug
Weight w/o cable	25 g

