

WAVE-15P

Order No. 0259016



Passive full range speaker system, 500 W, 8 Ω

- Full range bass-reflex system
- Robust plastic cabinet
- 38 cm (15") bass speaker with steel basket
- 25 mm (1") horn tweeter, 34 mm (1 3/8") voice coil diameter
- PTC tweeter protection
- M8 threaded inserts at the top and bottom
- 2 x SPEAKER jack, in/out
- Stand sleeve

Model	WAVE-15P
Total power rating	500 W
Power rating (RMS)	250 W
Impedance	8 Ω
Frequency range	55-20,000 Hz
SPL	96 dB/W/m
Beam angle	H: 90°/V: 60°
Dimensions	460 x 710 x 370 mm
Weight	15.8 kg



WAVE-12P

Order No. 0259015



Passive full range speaker system, 400 W, 8 Ω

- Full range bass-reflex system
- Robust plastic cabinet
- 30 cm (12") bass speaker with steel basket
- 25 mm (1") horn tweeter, 34 mm (1 3/8") voice coil diameter
- PTC tweeter protection
- M8 threaded inserts at the top and bottom
- 2 x SPEAKER jack, in/out
- Stand sleeve

Model	WAVE-12P
Total power rating	400 W
Power rating (RMS)	200 W
Impedance	8 Ω
Frequency range	55-20,000 Hz
SPL	95 dB/W/m
Beam angle	H: 90°/V: 60°
Dimensions	390 x 610 x 340 mm
Weight	13.6 kg



WAVE-10P

Order No. 0259014



Passive full range speaker system, 300 W, 8 Ω

- Full range bass-reflex system
- Robust plastic cabinet
- 25 cm (10") bass speaker with steel basket
- 25 mm (1") horn tweeter, 25 mm (1") voice coil diameter
- PTC tweeter protection
- M8 threaded inserts at the top and bottom
- 2 x SPEAKER jack, in/out
- Stand sleeve

Model	WAVE-10P
Total power rating	300 W
Power rating (RMS)	150 W
Impedance	8 Ω
Frequency range	60-20,000 Hz
SPL	95 dB/W/m
Beam angle	H: 90°/V: 60°
Dimensions	300 x 510 x 210 mm
Weight	7.5 kg



WAVE-08P

Order No. 0259013



Passive full range speaker system, 200 W, 8 Ω

- Full range bass-reflex system
- Robust plastic cabinet
- 20 cm (8") bass speaker with steel basket
- 25 mm (1") horn tweeter, 25 mm (1") voice coil diameter
- PTC tweeter protection
- M8 threaded inserts at the top and bottom
- 2 x SPEAKER jack, in/out
- Stand sleeve

Model	WAVE-08P
Total power rating	200 W
Power rating (RMS)	100 W
Impedance	8 Ω
Frequency range	65-20,000 Hz
SPL	95 dB/W/m
Beam angle	H: 90°/V: 60°
Dimensions	260 x 420 x 210 mm
Weight	5.8 kg

