


PAB-308/SW

Order No. 0254290



PAB-308/WS

Order No. 0254300



Universal PA speaker systems, 125 W, 8 Ω

- Compact 8/2 full range bass-reflex system
- 20 cm (8") bass speaker, 25 mm (1") horn tweeter
- Tweeter protection circuit
- High-quality MDF wooden cabinet in black (SW) or white (WS), with protective metal grille
- 4 x M8 threaded inserts for suspended installation

Model	PAB-308/SW, PAB-308/WS
Total power rating	250 W
Power rating (RMS)	125 W
Frequency range	60-20,000 Hz
SPL	93 dB/W/m
Dimensions	258 x 410 x 247 mm
Weight	7.5 kg
Inputs	1 x NEUTRIK SPEAKON
Outputs	1 x NEUTRIK SPEAKON par. out

- Supplied with mounting bracket and integrated stand sleeve
- NEUTRIK SPEAKON terminal



PAB-306/SW

Order No. 0254270



PAB-306/WS

Order No. 0254280



Universal PA speaker systems, 160 W, 8 Ω

- Closed 2-way system
- 2 x 16 cm (6.5") bass speaker, 25 mm (1") horn tweeter
- Tweeter protection circuit
- High-quality MDF wooden cabinets in black (SW) or white (WS), with protective metal grille

Model	PAB-306/SW, PAB-306/WS
Total power rating	320 W
Power rating (RMS)	160 W
Frequency range	65-20,000 Hz
SPL	93 dB/W/m
Dimensions	212 x 565 x 190 mm
Weight	9.5 kg
Inputs	1 x NEUTRIK SPEAKON
Outputs	1 x NEUTRIK SPEAKON, par. out

- 4 x M8 threaded inserts for suspended installation
- Supplied with mounting bracket and integrated stand sleeve
- NEUTRIK SPEAKON terminal



CLUB-1TOP

Order No. 0252490



Pair of professional PA speaker systems, 2 x 100 W/8 Ω

- 16 cm high-performance bass-midrange speaker with carbon fibre cone
- Waveguide dome tweeter
- NEUTRIK SPEAKON IN/OUT for an easy parallel connection
- High-quality lacquered MDF cabinet, full front grille with acoustic foam

Model	CLUB-1TOP
Total power rating	160 W
Power rating (RMS)	100 W
Frequency range	55-21,000 Hz
SPL	90 dB/W/m
Dimensions	210 x 300 x 260 mm
Weight	6 kg
Inputs	1 x NEUTRIK SPEAKON
Outputs	1 x NEUTRIK SPEAKON

- 6 x M8 threaded insert, 1 x standard stand sleeve



CLUB-1SUB

Order No. 0252480



Professional subwoofer, 600 W/8 Ω or 2 Ω or 2 x 300 W/4 Ω

- 4 x 20 cm (8") top-class woofer
- Variable impedance concept (switchable between 1 x 8 Ω and 2 x 4 Ω, for parallel connection in the 2 x 4 Ω position as 1 x 2 Ω)
- High-quality lacquered MDF cabinet, full front grille with acoustic foam
- An amplifier with integrated or external active crossover network is required for operation

Model	CLUB-1SUB
Total power rating	1,200 W
Power rating (RMS)	600 W
Frequency range	45-250 Hz
SPL	96 dB/W/m
Dimensions	300 x 880 x 440 mm
Weight	29.5 kg
Inputs	1 x or 2 x NEUTRIK SPEAKON, switchable



SUB-10

Order No. 0259875



Passive subwoofer, 500 W/8 Ω

- Band-pass subwoofer with double ventilation
- 1 x 25 cm (10") top-class woofer
- Slimline and compact design for upright and horizontal setup
- High-quality lacquered cabinet made of plywood, front grille with inner lining
- Integrated crossover network (low-pass) with crossover frequency at 200 Hz

Model	SUB-10
Total power rating	500 W
Power rating (RMS)	250 W
Frequency range	40-200 Hz
SPL	92 dB/W/m
Dimensions	300 x 610 x 410 mm
Weight	19.84 kg
Inputs	1 x NEUTRIK SPEAKON, speaker terminals

