

WSA-50WIFI

Order No. 0257160

**WLAN audio receiver,**

for audio streaming from your smartphone, tablet PC, stationary PC or Mac. The device receives audio signals via network and then transmits them to a stereo system or an active speaker via cable.

- Audio streaming directly from any device
- Operating modes: Access Point (AP) or Station (STA)
- WLAN standard: IEEE802.11a/b/g/n
- DLNA, AirPlay
- File formats: e.g. MP3, FLAC, WAV, APE, WMA, AAC
- Data transmission rate: up to 7 Mbps
- Integrated browser
- Free app available, e.g. iMediaShare
- LED status indication
- Volume level control
- Analogue line level output via 6.3 mm jacks L/R and 3-pole XLR L/R

Model	WSA-50WIFI
Frequency range	20-20,000 Hz
THD	≤ 0.1%
Channel separation	≥ 90 dB
Operating range	> 20 m (AP) > 50 m (STA)
Power supply	via encl. power supply
Dimensions	130 x 54 x 130 mm
Weight	516 g
Connections	Outputs: 1 x 6.3 mm stereo jack L/R, analogue 1 x 3-pole XLR L/R, analogue
Other features	DLNA, AirPlay, HTTP

- Metal housing
- Power is provided via enclosed plug-in power supply

**WSA-24T**

Order No. 0257150

Wireless stereo transmitter, 2.4 GHz, for audio streaming.

- Matching the receiver WSA-24R
- Stereo/mono selector switch
- LED for indicating status and peak
- Interference-free operation due to FHSS technology (Frequency Hopping Spread Spectrum)
- Analogue line level input via 6.3 mm jacks L/R and 3-pole XLR L/R
- Metal housing
- Power is provided via enclosed plug-in power supply

Model	WSA-24T
Frequency range	20-20,000 Hz
THD	< 0.3%
Channel separation	≥ 90 dB
Operating range	> 30 m, without any obstacles
Power supply	via encl. power supply
Dimensions	130 x 54 x 130 mm
Weight	470 g
Connections	Inputs: 1 x 6.3 mm stereo jack L/R, analogue 1 x 3-pole XLR L/R, analogue
Other features	2.4 GHz, 25 channels, latency: 18 ms

**WSA-24R**

Order No. 0257140

Wireless stereo receiver, 2.4 GHz, for audio streaming.

- Matching the transmitter WSA-24T
- Interference-free operation due to FHSS technology (Frequency Hopping Spread Spectrum)
- Analogue line level output via 6.3 mm jacks L/R
- Plastic housing
- Power is provided via enclosed plug-in power supply

Model	WSA-24R
Frequency range	20-20,000 Hz
THD	< 0.3%
Channel separation	≥ 90 dB
Power supply	via encl. power supply
Dimensions	116 x 35 x 86 mm
Weight	118 g
Connections	Outputs: 1 x 6.3 mm stereo jack L/R, analogue
Other features	2.4 GHz, 25 channels, latency: 18 ms

