

Tender text

MPR-1

1-channel microphone preamplifier,

with switchable phantom power.

- 1 microphone input, XLR, bal. or 6.3 mm jack, bal.
- Gain control: up to 50 dB max.
- Clip LED
- 30 V phantom power, can be activated as required

Specifications:

| | |
|-----------------------|--|
| Description | microphone preamplifier |
| Frequency range | 10-30,000 Hz |
| Input signal | 3.5 mV (XLR, bal.) 16 mV (jack, bal.) |
| Input impedance | 10 k Ω |
| Output signal | 1 V |
| Gain | 50 dB (with bal. connection) 44 dB (with unbal. connection) |
| S/N ratio | 58 dB |
| THD | 0.1% |
| Admiss. ambient temp. | 0-40 °C |
| Power supply | via encl. plug-in power supply |
| Dimensions | 113 x 92 x 40 mm |
| Weight | 345 g |
| Inputs | 1 x XLR, 1 x 6.3 mm jack |
| Outputs | 1 x XLR, 1 x 6.3 mm jack |

Brand: IMG STAGELINE

Type: MPR-1

Quantity: 1

Packing dimensions (W x H x L): 0.11 x 0.065 x 0.24 m

Gross weight: 0.67 kg

Net weight: 0.53 kg

Item weight (w/o accessories): 0.345 kg