

Tender text

STA-300D

Stereo class D PA amplifier

- 2 operating modes can be selected (stereo or bridged)
- Limiter function can be activated as required
- 2 level controls
- Temperature-controlled fan
- Protective circuit with LED indication for protection against short circuit, overheating and DC voltage overlay at the outputs
- Each channel with LEDs for indicating overload (clip) and signal

Specifications:

| | |
|--|--|
| Peak output power | 350 W |
| Power rating | 300 W |
| Power rating at 4 Ω | 2 x 150 W |
| Power rating at 8 Ω | 2 x 100 W |
| Power rating with 8 Ω bridged operation | 1 x 300 W |
| Channels | 2 |
| Inputs | 1 V/12 k Ω |
| Frequency range | 20-20,000 Hz |
| Integrated limiter | yes |
| S/N ratio | > 96 dB |
| Crosstalk attenuation | > 70 dB |
| THD | < 0.05% |
| Mains voltage | ~ 230 V |
| Mains frequency | 50 Hz |
| Power consumption, operation | 510 VA |
| Admiss. ambient temp. | 0-40 °C |
| Width | 482 mm |
| Height | 52 mm |
| Depth | 290 mm |
| Rack spaces, RS | 1 |
| Weight | 3.7 kg |
| Connections | 1 x 3-pole XLR L/R 1 x 6.3 mm jack L/R 1 x SPEAKER L/R |
| Packing dimensions (W x H x L) | 0.38 x 0.12 x 0.55 m |
| Gross weight | 4.75 kg |
| Net weight | 3.84 kg |

Brand: IMG STAGELINE

Type: STA-300D

Quantity: 1

Packing dimensions (W x H x L): 0.38 x 0.12 x 0.55 m

Gross weight: 4.75 kg

Net weight: 3.84 kg

Item weight (w/o accessories): 3.7 kg