

Tender text

STA-400D

Stereo class D PA amplifier

- Class D concept with power amplifier modules from HYPEx
- 482 mm (19") rack installation, 1 RS, with supplied mounting brackets
- Silent operation due to temperature-controlled fans
- Lightweight design due to compact switch-mode power supply
- Energy-efficient concept due to a high efficiency
- Powerful bass reproduction due to large buffer capacitors (high power reserves)
- 2 level controls
- Protected against short circuit and overtemperature
- LEDs for indicating power, overload (clip) and protect
- Super slimline design
- NEUTRIK SPEAKON connections

Specifications:

Peak output power	700 W
Power rating	540 W
Power rating at 4 Ω	2 x 270 W
Power rating at 8 Ω	2 x 180 W
Channels	2
Inputs	1 V/10 kΩ (XLR, bal.), 1 V/4.7 kΩ (RCA)
Frequency range	20-20,000 Hz
Integrated limiter	no
S/N ratio	> 110 dBA
THD	< 0.02%
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	600 VA
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	52 mm
Depth	277 mm
Rack spaces, RS	1
Weight	3.5 kg
Connections	1 x 3-pole XLR L/R 1 x RCA L/R 1 x NEUTRIK SPEAKON L/R 2 x pair of screw terminals

Brand: IMG STAGELINE

Type: STA-400D

Quantity: 1

Packing dimensions (W x H x L): 0.32 x 0.095 x 0.53 m

Gross weight: 4.31 kg

Net weight: 3.56 kg

Item weight (w/o accessories): 3.5 kg