

Tender text

TXS-2402SET

Digital wireless 2-channel PLL microphone system, 2.4 GHz

- 2 microphone transmitters, 1 receiver, 1 plug-in PSU
- High resistance to interference due to digital transmission
- 2 systems can be used in parallel (corresponds to 4 microphone transmission paths)
- 16 frequencies (2,404-2,476 MHz) for each channel can be selected at the transmitter
- Wireless auto-configuration of the receiver
- Volume control for each channel
- 6.3 mm output for mixed signal
- Microphone cartridges of supercardioid characteristic

Licence-free in the EU.

Specifications:

General information

| | |
|----------------------------|---|
| Description | wireless microphone system |
| Carrier frequency range | 2,404-2,476 MHz |
| Audio frequency range | 80-12,000 Hz |
| Channels | 2 |
| THD | < 0.1% |
| Dynamic range | 87 dB |
| Admiss. ambient temp. | 0-40 °C |
| Specifications transmitter | |
| Transmitting power | 10 mW |
| Operating range | approx. 30 m (free field) approx. 20 m (indoors) |
| Power supply transmitter | 2 x 1.5 V batt. AA size |
| Width transmitter | 54 mm |
| Height transmitter | 54 mm |
| Depth transmitter | 225 mm |
| Weight transmitter | 120 g |
| Specifications receiver | |
| Audio signal receiver | 100 mV/600 Ω |
| Power supply receiver | via encl. plug-in power supply |
| Width receiver | 220 mm |
| Height receiver | 45 mm |
| Depth receiver | 150 mm |
| Weight receiver | 550 g |
| Connections receiver | 1 x 6.3 mm jack, unbal. |

Brand: IMG STAGELINE

Type: TXS-2402SET

Quantity: 1

Packing dimensions (W x H x L): 0.28 x 0.065 x 0.345 m

Gross weight: 1.516 kg

Net weight: 1.066 kg

Item weight (w/o accessories): 1.066 kg