

Tender text

TXS-606DT/2

Wireless desktop microphone with integrated multifrequency transmitter,

with UHF PLL technology.

- Electret microphone cartridge, cardioid polar pattern
- 350 mm gooseneck, removable
- 800 selectable UHF frequencies (672.000-691.975 MHz), can be synchronised with receivers TXS-606, TXS-626, TXS-646 or TXS-686 via ACT function
- Adjustable sensitivity
- Switchable transmitting power (high: 25 mW/low: 2.5 mW)
- LCD for indicating group/channel, audio level and battery status
- Power supply via 2 x 1.5 V battery AA size (not supplied)

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section “IMPORTANT INFORMATION”!

Specifications:

Description	microphone desk stand transmitter
Transmission method	wireless
Polar pattern	cardioid
System	electret
Carrier frequency range	672.000-691.975 MHz
Transmitting power	25 mW/2.5 mW
Power supply	2 x 1.5 V batt. AA size
Operating time	> 8 h
Audio frequency range	30-18,000 Hz
Admiss. ambient temp.	0-40 °C
Dimensions	120 x 65 x 178 mm (w/o gooseneck)
Weight	1.2 kg
Packing dimensions (W x H x L)	0.175 x 0.085 x 0.515 m
Gross weight	1.677 kg
Net weight	1.296 kg

Brand: IMG STAGELINE

Type: TXS-606DT/2

Quantity: 1

Packing dimensions (W x H x L): 0.175 x 0.085 x 0.515 m

Gross weight: 1.677 kg

Net weight: 1.296 kg

Item weight (w/o accessories): 1.2 kg