

Tender text

TXS-606LT/2

Multifrequency tie clip microphone transmitter,

with UHF PLL technology.

- 800 selectable UHF frequencies (672.000-691.975 MHz), can be synchronised with receivers TXS-606, TXS-626, TXS-646 or TXS-686 via ACT function
- Continuously adjustable sensitivity
- LCD for indicating group/channel, audio level and battery status
- Tie clip microphone with latchable 3.5 mm plug
- Belt clip
- Power supply via 2 x 1.5 V battery AA size (not supplied)

There are restrictions or requirements within the EU!

Please read the information regarding wireless systems in the section "IMPORTANT INFORMATION"!

Specifications:

General information

Description	pocket transmitter
Carrier frequency range	672.000-691.975 MHz
Audio frequency range	30-18,000 Hz
Channels	1
Operating time	> 8 h
Admiss. ambient temp.	0-40 °C
Specifications transmitter	
Transmitting power	10 mW
Power supply transmitter	2 x 1.5 V batt. AA size
Width transmitter	61 mm
Height transmitter	106 mm
Depth transmitter	27 mm
Weight transmitter	96 g
Connections transmitter	1 x 3.5 mm jack

Brand: IMG STAGELINE

Type: TXS-606LT/2

Quantity: 1

Packing dimensions (W x H x L): 0.155 x 0.065 x 0.19 m

Gross weight: 0.243 kg

Net weight: 0.096 kg

Item weight (w/o accessories): 0.096 kg