



LMS-808

Order No.: 0202160

PRODUCTINFOS

Microphone line mixer/line splitter

- Multifunctional device with three selectable operating modes:
 - Mixer operation for mixing up to 8 mono input signals (6 x line/mic and 2 x line) to 1 stereo output
 - Line splitter operation for splitting 2 mono line inputs to 6 mono outputs
 - Level matching amplifier operation for boosting up to 6 input signals
- 6 mono input channels, each with switchable 12 V phantom power, pan pot, signal/clip LED and individual selection of the operating mode
- 2 mono line input channels, each with level control and signal/clip LED

TECHNICAL SPECIFICATIONS

LMS-808

No. of channels	8
No. of inputs	8
Mic input	1 mV/6.6 k Ω (mic), 6 x XLR, bal.
Line input	250 mV/30 k Ω , 2 x XLR, bal. 100 mV/40 k Ω , 6 x XLR, bal.
Master output	1 V/200 Ω , 6 x XLR, bal. (mono), 1 x XLR L/R, bal. (stereo)
Frequency range	10-30,000 Hz

LMS-808

THD	0.02%
S/N ratio	81 dB, weighted
Crosstalk	-63 dB
Power supply	~ 230 V/50 Hz/10 VA
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	10 VA
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	48 mm
Depth	200 mm
Rack units, RU	1
Weight	2.9 kg
Packing dimensions (W x H x L)	0.25 x 0.09 x 0.535 m
Gross weight	3.88 kg
Net weight	3.14 kg