



# LMS-808

Order No.: 0202160

## PRODUCTINFOS

### Microphone line mixer/line splitter

- Multifunctional device with three selectable operating modes:
- Mixer operation for mixing up to 8 mono input signals (6 x line/mic and 2 x line) to 1 stereo output
- Line splitter operation for splitting 2 mono line inputs to 6 mono outputs
- Level matching amplifier operation for boosting up to 6 input signals
- 6 mono input channels, each with switchable 12 V phantom power, pan pot, signal/clip LED and individual selection of the operating mode
- 2 mono line input channels, each with level control and signal/clip LED

## TECHNICAL SPECIFICATIONS

### LMS-808

No. of channels	8
No. of inputs	8
Mic input	1 mV/6.6 k $\Omega$ (mic), 6 x XLR, bal.
Line input	250 mV/30 k $\Omega$ , 2 x XLR, bal. 100 mV/40 k $\Omega$ , 6 x XLR, bal.
Master output	1 V/200 $\Omega$ , 6 x XLR, bal. (mono), 1 x XLR L/R, bal. (stereo)
Frequency range	10-30,000 Hz

**LMS-808**

THD	0.02%
S/N ratio	81 dB, weighted
Crosstalk	-63 dB
Power supply	~ 230 V/50 Hz/10 VA
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	10 VA
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	48 mm
Depth	200 mm
Rack spaces, RS	1
Weight	2.9 kg