

PPA-100/SW

Order No.: 0244190

PRODUCTINFOS

Stereo headphone amplifier

- 6 separate headphone amplifiers, each with 1 level control and 1 signal/clip LED as well as main/solo switching
- 1 input (solo) per amplifier, switchable to common main input (main)
- Main input with low/high selector switch for matching the input signal
- Inputs: solo (stereo) 6 x 6.3 mm jack, main (stereo) 2 x 6.3 mm jack, 2 x RCA L/R
- Outputs: headphones (stereo) 6 x 6.3 mm jack

TECHNICAL SPECIFICATIONS

PPA-100/SW	
Description	headphone amplifier
Frequency range	5-30,000 Hz
Input signal	250 mV/50 kΩ (solo) 250 mV/50 kΩ (main low) 2.2 V/60 kΩ (main high)
Output signal	2 x 16 mW/8 Ω 2 x 45 mW/32 Ω 2 x 75 mW/600 Ω
S/N ratio	> 60 dB
Channel separation	50 dB
THD	0.02%
Admiss. ambient temp.	0-40 °C

PPA-100/SW

Power supply	˜ 230 V/50 Hz/11 VA
Dimensions	482 x 44 x 185 mm, 1 RS
Weight	2.3 kg
Inputs	2 x RCA L/R (main), 2 x 6.3 mm jack (main), 6 x 6.3 mm jack (solo)
Outputs	6 x 6.3 mm jack (headphones)