



FLAT-M200

Order No.: 0259876

PRODUCTINFOS

Active PA stage monitor speaker system, 300 W

- Flat and very compact full range system
- Fitted with 4 x 10 cm (FaitalPRO, 4 x 4") full range speaker with neodymium magnets
- Class D amplifier system
- Sound pressure at nominal power: 122 dB
- Indication of signal and limiter
- Volume control and tone control
- Balanced line/mic input and feed-through output
- High-quality multiplex wooden cabinet with protective metal grille
- 2 x M10 and 2 x M6 threaded inserts for stand adapter or mounting device
- Supplied with clamp for mounting, e.g. onto a microphone stand

TECHNICAL SPECIFICATIONS

FLAT-M200

Active/passive	active
Transmission method	cable

FLAT-M200

Total output power	300 W
Power rating (RMS)	200 W
Frequency range	70-20,000 Hz
Input signal	25 mV/28 kΩ (line, bal.), 6 mV/20 kΩ (mic, bal.)
System	4 x 4", full range
Full range speaker	4 x 10 cm (FaitalPRO 4 x 4") full range speaker
Number of speakers	4
Speaker size	10 cm (4")
Sensitivity	98 dB/W/m
Max. rated SPL	122 dB
Housing material	multiplex
Colour	black
Mounting device	2 x M10 threaded insert, 2 x M6 threaded insert
Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/356 VA
Dimensions	320 x 150 x 250 mm
Width	320 mm
Height	150 mm
Depth	250 mm
Weight	4.11 kg
Inputs	1 x comb. XLR/6.3 mm (line/mic)
Outputs	1 x XLR link out
Other features	limiter
Accessories	FLAT-M200BAG
Packing dimensions (W x H x L)	0.35 x 0.17 x 0.35 m
Gross weight	4.82 kg
Net weight	4.11 kg