



TXS-812SET

Order No.: 0252600

PRODUCTINFOS

Wireless 2-channel microphone system

- 2 microphone transmitters, 1 receiver, 1 plug-in power supply
- Two-channel UHF version (non-diversity) with channel mixing function which can additionally be selected
- Volume and squelch controls for each channel
- Each channel with LEDs for indicating RF signal and audio signal

Licence-free in the EU.

TECHNICAL SPECIFICATIONS

TXS-812SET

General information

| | |
|-------------------------|----------------------------|
| Description | wireless microphone system |
| Carrier frequency range | 863.80 MHz , 864.20 MHz |
| Audio frequency range | 40-15,000 Hz |

TXS-812SET

| | |
|----------------------------|---|
| Channels | 2 |
| THD | < 0.5% |
| Dynamic range | > 90 dB |
| RF S/N ratio | > 80 dB |
| Admiss. ambient temp. | 0-40 °C |
| Specifications transmitter | |
| Transmitting power | < 10 mW |
| Operating range | approx. 30 m |
| Power supply transmitter | 2 x 1.5 V batt. AA size (not supplied) |
| Width transmitter | 52 mm |
| Height transmitter | 52 mm |
| Depth transmitter | 260 mm |
| Weight transmitter | 240 g |
| Specifications receiver | |
| Audio signal receiver | 0-200 mV/10 kΩ (jack) 0-400 mV/10 kΩ (XLR, bal.) |
| Power supply receiver | via encl. plug-in power supply |
| Width receiver | 210 mm |
| Height receiver | 46 mm |
| Depth receiver | 190 mm |
| Weight receiver | 560 g |
| Connections receiver | 2 x XLR, bal. 1 x 6.3 mm jack, unbal. |