



DM-5000LN

Order No.: 0230400

PRODUCTINFOS

These microphones

are especially optimised for vocal and speech applications on stage and are thus provided with cartridges of particularly high efficiency (high sensitivity). However, in an environment with extra loud diffuse sound fields, e.g. discotheques, there is a greater possibility of acoustic feedback than at more basic microphones due to this high sensitivity.

Dynamic microphone,

for stage and vocals.

- Supercardioid polar pattern
- Highly sensitive neodymium magnet version
- Supplied with microphone holder, cable and case

PROSOUND

“A suitable solution, ... a well-balanced microphone with an appealing sound.”

tools4music

“... as to sound, the microphone shamelessly turns the test field upside down.”

TECHNICAL SPECIFICATIONS**DM-5000LN**

Description	vocal microphone
Transmission method	cable
Polar pattern	supercardioid
System	dynamic
Audio frequency range	40-18,000 Hz
Nominal impedance	250 Ω
Sensitivity	2.5 mV/Pa
Max. sound pressure	130 dB
Housing material	diecast zinc
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 53.5 mm x 174 mm
Weight	690 g
Cable	6 m, low-noise, XLR
Connection	XLR, bal.
Packing dimensions (W x H x L)	0.145 x 0.07 x 0.24 m
Gross weight	1.13 kg
Net weight	0.79 kg