



DMIX-20

Order No.: 20.2890

Price upon request

PRODUCTINFOS

A Mixer for Creative Users ...

The digital mixer DMIX-20 from IMG STAGELINE impresses with an intuitive operating concept of the well thought-out user surface. Due to the compact design, it is also ideally suited for applications on smaller to medium-sized stages and for your home studio. The device quickly impresses musicians, DJs and live sound mixers. Combined with an external router, the DMIX-20 also allows for a convenient operation via iPad using a network connection. The free app can be downloaded from the app store.

The console features 16 mono input channels and 2 stereo input channels as well as +48 V phantom power. The 8 outputs can either be used as 4 aux paths and 4 subgroup paths or as 8 aux outputs. It features 2 integrated DSPs with 12 types of effects, noise gate, compressor/limiter, delay and a 100 mm motor-driven fader.

The colour LCD touch screen facilitates operation with your settings which can easily be stored thanks to modern digital technology. Thus, you are able to store the channel's sound adjustments via parametric equalizer, graphic equalizer or use the options of the effect unit. Furthermore, the digital mixer enables you to store 24 overall settings. The full duplex port allows for simultaneous recording and reproduction from a PC or onto a PC. It is also equipped with two headphone outputs.

19-channel digital audio mixer,



with touch screen, 2 DSP effect units and USB interface.

- 16 mono input channels with assignable controls
- 8 channel inserts
- 2 stereo input channels
- 1 USB audio channel
- Full duplex USB port (allows for simultaneous recording and reproduction) for reproduction of digital audio data from a PC and for recording mixings onto a PC
- 2 integrated DSPs as well as equalizer, noise gate, compressor/limiter and delay
- 4 aux send outputs and 4 subgroup outputs or 8 aux outputs
- 6 DCA groups
- Control room function
- 100 mm motor-driven fader
- Sampling rate: 24 bits/48 kHz
- Settings can be stored
- Remote control possible via iPad (when connected to external router)
- RJ45 network connection for remote control
- +48 V phantom power
- 2 adjustable headphone outputs
- 17.8 cm colour LCD touch screen (7") for display and settings
- Mounting facility for extension modules available at option
- 482 mm (19") rack installation, 8 RS, with supplied mounting brackets

EVENT Rookie 05/2016

"The DMIX-20 is available for less than 1,000 Euros but you'll get a live console with fantastic features for your band or studio: everyone was sceptical at first about the operation with one fader only, but absolutely impressed after just a few minutes. The compact design allows you to place the console anywhere on stage; the number of channels available is more than sufficient and the device provides ample possibilities for its size."

TECHNICAL SPECIFICATIONS

DMIX-20

No. of channels 19 No. of inputs 19

Mic input 3 mV, bal. (combo jack)

750 mV, bal. (stereo),

Line input 100 mV (mono)

Insert input 800 mV



DMIX-20

750 mV, bal. (XLR) Master output 750 mV (jack)

8 V Aux output

Insert output 800 mV 2.3 V Control room Headphones > 8 Ω USB yes

Frequency range 20-20,000 Hz THD < 0.01% S/N ratio > 104 dB Crosstalk > 80 dB

Equalizer bass ±24 dB/21-19,200 Hz (dep. on filter)

±24 dB/21-19,200 Hz (dep. on filter)

Equalizer midrange ±24 dB/21-19,200 Hz (dep. on filter)

Equalizer treble ±24 dB/21-19,200 Hz (dep. on filter)

equalizer DSP Phantom power +48 V

Power supply ~ 230 V/50 Hz/60 VA

~ 230 V Mains voltage Mains frequency 50 Hz Power consumption, operation 60 VA 0-40 °C Admiss. ambient temp. Width 442 mm 130 mm Height Depth 355 mm Weight 7.3 kg