



MXR-40PRO

Order No.: 0200490

PRODUCTINFOS

Professional 4-channel audio mixer,

with DSP effect unit, integrated MP3 player and Bluetooth receiver.

- Integrated USB audio interface (will be identified and addressed as an external sound card)
- Full-duplex USB port (allows for simultaneous recording and reproduction) for reproduction of digital audio data from a PC and for recording mixings onto a PC
- 2 mono input channels with gain control, 3-way equalizer and pan pot
- 1 stereo input channel with 3-way equalizer and balance control
- MP3 player
- USB port
- Bluetooth receiver
- 16 different DSP effects
- Adjustable aux return input and FX send output
- +48 V phantom power, can be activated as required
- Adjustable headphone output
- Stereo LED level display

TECHNICAL SPECIFICATIONS

MXR-40PRO

| | |
|--------------------------------|---|
| Input channels | 4 |
| Number of mix/mono | 2 |
| No. of stereo | 1 |
| Mic input | 0.6 mV, bal. 2 x XLR |
| Line input | 80 mV (stereo), 1 x 6.3 mm jack L/R 7 mV (mono), 2 x 6.3 mm jack |
| Aux input | 340 mV, 1 x 6.3 mm jack L/R |
| Master output | 760 mV, 1 x 6.3 mm jack L/R |
| Effect send | 9 V, 1 x 6.3 mm jack |
| Headphones | $\geq 8 \Omega$, 1 x 6.3 mm jack |
| USB | yes |
| Bluetooth | yes |
| Frequency range | 20-20,000 Hz |
| THD | < 0.03% |
| S/N ratio | > 75 dB(A) |
| Equalizer bass | ± 15 dB/80 Hz |
| Equalizer midrange | ± 15 dB/2.5 kHz |
| Equalizer treble | ± 15 dB/12 kHz |
| Phantom power | +48 V |
| Power supply | ~ 230 V/50 Hz/15 VA |
| Mains voltage | ~ 230 V |
| Mains frequency | 50 Hz |
| Power consumption, operation | 15 VA |
| Admiss. ambient temp. | 0-40 °C |
| Width | 282 mm |
| Height | 93 mm |
| Depth | 320 mm |
| Weight | 2.7 kg |
| Packing dimensions (W x H x L) | 0.33 x 0.375 x 0.135 m |
| Gross weight | 3.17 kg |
| Net weight | 2.73 kg |