



STA-235

Order No.: 0253210

PRODUCTINFOS

Stereo PA amplifier,

with integrated limiter.

- LCD for indicating temperature, operating mode, power
- 2 operating modes can be selected (stereo or bridged)
- Limiter function can be activated as required
- Temperature-controlled fans
- 2 level controls
- Ground lift function
- Speaker switch-on delay
- Protective circuit with LED indication for protection against short circuit and overheating
- Each channel with LEDs for indicating overload, level and signal

TECHNICAL SPECIFICATIONS

STA-235

| | |
|---|-------------|
| Peak output power | 1,400 W |
| Power rating | 1,000 W |
| Power rating at 4 Ω | 2 x 500 W |
| Power rating at 8 Ω | 2 x 400 W |
| Power rating with 8 Ω bridged operation | 1 x 1,000 W |

STA-235

| | |
|--------------------------------|-----------------------------|
| Channels | 2 |
| Inputs | 1.2 V/10 kΩ |
| Frequency range | 10-50,000 Hz |
| Integrated limiter | yes |
| S/N ratio | > 80 dB |
| Crosstalk attenuation | > 50 dB |
| THD | < 0.1% |
| Mains voltage | ~ 230 V |
| Mains frequency | 50 Hz |
| Power consumption, operation | 2,000 Hz |
| Admiss. ambient temp. | 0-40 °C |
| Width | 482 mm |
| Height | 100 mm |
| Depth | 330 mm |
| Rack units, RU | 2 |
| Weight | 11.5 kg |
| Connections | 1 x 3-pole XLR L/R, bal. |
| | 1 x 6.3 mm jack L/R, bal. |
| | 3 x SPEAKER |
| | 2 x pair of screw terminals |
| Packing dimensions (W x H x L) | 0.37 x 0.14 x 0.51 m |
| Gross weight | 13.52 kg |
| Net weight | 12.6 kg |