



MEQ-115/SW

Order No.: 0244350

PRODUCTINFOS

Graphic equalizer

- 2-channel version, 2 x 15 frequency controls in 2/3 octave steps
- Switchable control range $\pm 6/\pm 12$ dB
- Peak LED
- Switchable low cut filter
- Master volume control
- Bypass switch and ground lift switch
- Frequency controls with centre click
- Inputs and outputs each via 2 x XLR and 2 x 6.3 mm jack

TECHNICAL SPECIFICATIONS

MEQ-115/SW

Description	graphic equalizer
Frequency range	20-20,000 Hz
Control range	switchable $\pm 6/\pm 12$ dB
Control frequencies	2 x 25/40/63/100/160/250/400/630 Hz/ 1/1.6/2.5/4/6.3/10/16 kHz
Input signal	0.775 V
Input impedance	50 k Ω
Output signal	0.775 V
Output impedance	600 Ω
Low cut	20 Hz/-3 dB

MEQ-115/SW

S/N ratio	66 dB
THD	< 0.1%
Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/10 VA
Dimensions	482 x 44.5 x 165 mm, 1 RU
Weight	2.5 kg
Inputs	2 x XLR, 2 x 6.3 mm jack
Outputs	2 x XLR, 2 x 6.3 mm jack