



TXS-611SET

Order No.: 0253650

PRODUCTINFOS

Multifrequency microphone system,

with UHF PLL technology.

- 1 hand-held microphone transmitter (cardioid polar pattern), 1 receiver, 1 plug-in power supply
- True diversity system
- 80 selectable UHF channels (863-865 MHz)
- ACT function for transmitting selected frequency to the hand-held microphone via infrared signal
- Auto-scan
- Volume and squelch controls
- Transmitting power can be switched at the hand-held microphone (high/low)
- Indication for channel, antenna A/B, ACT status and AF audio level (receiver), channel and battery status (hand-held microphone)
- Robust metal housing (receiver)

Licence-free system in the EU.

TECHNICAL SPECIFICATIONS

TXS-611SET

General information

Description wireless microphone system

Carrier frequency range 863-865 MHz

Audio frequency range 50-18,000 Hz

Channels 1

THD < 0.5%

Dynamic range 120 dB

RF S/N ratio 105 dB

Admiss. ambient temp. 0-40 °C

Specifications transmitter

Transmitting power < 10 mW

Operating range ≈ 30 m

Power supply transmitter 2 x 1.5 V batt. AA size

Width transmitter 52 mm

Height transmitter 52 mm

Depth transmitter 275 mm

Weight transmitter 235 g

Specifications receiver

Audio signal receiver 350 mV/10 kΩ (jack)
25 mV/10 kΩ (XLR, bal.)

Power supply receiver via encl. plug-in power supply

Width receiver 152 mm

Height receiver 38 mm

Depth receiver 120 mm

Weight receiver 482 g

Connections receiver 1 x 6.3 mm jack, unbal.
1 x XLR, bal.