



TXS-2402SET

Order No.: 25.4090

Price upon request

PRODUCTINFOS

With the TXS-2402SET,

the entry into the world of digital wireless transmission will become a special sound experience. The signal transmission in the 2.4 GHz range is particularly stable and impresses by a high resistance to interference. The system manages without a compander which results in an incredibly dynamic efficiency and a voice transmission with a unique sound quality. Two systems can be used in parallel operation, thus 4 microphone transmission paths can be used simultaneously. Licence-free system. The particularly easy and convenient use of the units and appealing design make the TXS-2402SET a real digital experience for the user.

Digital wireless 2-channel PLL microphone system, 2.4 GHz

- 2 microphone transmitters, 1 receiver, 1 plug-in PSU
- High resistance to interference due to digital transmission
- 2 systems can be used in parallel (corresponds to 4 microphone transmission paths)
- 16 frequencies (2,404-2,476 MHz) for each channel can be selected at the transmitter
- Wireless auto-configuration of the receiver
- Volume control for each channel
- 6.3 mm output for mixed signal
- Microphone cartridges of supercardioid characteristic

Licence-free in the EU.

tastenwelt 06/2012

“An entry-level wireless system with a perfectly functioning technology.”

+ Easy operation

+ Well-balanced hand-held transmitter

TECHNICAL SPECIFICATIONS

TXS-2402SET

General information

Description	wireless microphone system
Carrier frequency range	2,404-2,476 MHz
Audio frequency range	80-12,000 Hz
Channels	2
THD	< 0.1%
Dynamic range	87 dB
Admiss. ambient temp.	0-40 °C

Specifications transmitter

Transmitting power	10 mW
Operating range	approx. 30 m (free field) approx. 20 m (indoors)
Power supply transmitter	2 x 1.5 V batt. AA size
Width transmitter	54 mm
Height transmitter	54 mm
Depth transmitter	225 mm
Weight transmitter	120 g

Specifications receiver

Audio signal receiver	100 mV/600 Ω
Power supply receiver	via incl. plug-in power supply
Width receiver	220 mm
Height receiver	45 mm
Depth receiver	150 mm
Weight receiver	550 g
Connections receiver	1 x 6.3 mm jack, unbal.