



## TXS-606

Order No.: 0253510

### PRODUCTINFOS

#### Multifrequency receiver unit,

with UHF PLL technology.

- 1,000 selectable UHF frequencies (672.000-696.975 MHz) in 10 groups with 100 frequencies each
- ACT function for transmitting selected frequency to pocket transmitter TXS-606HSE/2, tie clip microphone transmitter TXS-606LT/2, desktop microphone transmitter TXS-606DT/2 or hand-held microphone TXS-606HT/2 via infrared signal
- Auto-scan
- True diversity system with removable antennas (BNC connection)
- Volume and squelch controls
- LCD for indicating group/channel, antenna A/B, RF receiving level and AF audio level
- Additional LED level display for indicating audio level
- XLR output and 6.3 mm output
- 8 V supply voltage for active antennas or antenna amplifier (e.g. TXS-875B) is available
- Robust metal housing
- Supplied with power supply

**There are restrictions or requirements within the EU!**

Please read the notes regarding wireless systems in the section “IMPORTANT INFORMATION”!

## TECHNICAL SPECIFICATIONS

### TXS-606

#### General information

Description	receiver unit
Carrier frequency range	672.000-696.975 MHz
Audio frequency range	30-18,000 Hz
Channels	1
THD	< 0.5%
Dynamic range	100 dB
RF S/N ratio	105 dB
Admiss. ambient temp.	0-40 °C
Specifications receiver	
Audio signal receiver	350 mV/600 Ω (jack) 25 mV/600 Ω (XLR, bal.)
Power supply receiver	via encl. plug-in power supply
Width receiver	212 mm
Height receiver	45 mm
Depth receiver	180 mm
Weight receiver	930 g
Connections receiver	1 x XLR, bal., 1 x 6.3 mm jack, unbal.