



TXS-606HT/2

Order No.: 1000185

PRODUCTINFOS

Hand-held microphone with integrated multifrequency transmitter,

with UHF PLL technology.

- Dynamic microphone cartridge, cardioid polar pattern
- 800 selectable UHF frequencies (672.000-691.975 MHz), can be synchronised with receivers TXS-606, TXS-626, TXS-646 or TXS-686 via ACT function
- Adjustable sensitivity
- Switchable transmitting power (high: 25 mW/low: 2.5 mW)
- LCD for indicating group/channel, audio level and battery status
- Power supply via 2 x 1.5 V battery AA size (not supplied)

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

SOUNDCHECK 04/2012

"The TXS-646 can receive four wireless channels at the same time - the hand-held transmitter provides a

warm and powerful sound and stands its ground among the instruments ... the earband microphones allow for unobtrusive miking with both a low susceptibility to acoustic feedback and an excellent speech intelligibility ... the quad wireless system from IMG Stage Line provides a reliable operation at all times, is easy to use and impresses by a crisp sound.”

+ Clear sound

+ Very good price-performance ratio

+ Future-proof frequency range

(Test setup consisted of TXA-646 with TXS-606HT, TXS-606LT and HSE-70A/SK)

TECHNICAL SPECIFICATIONS

TXS-606HT/2

Description	hand-held microphone transmitter
Transmission method	wireless
Polar pattern	cardioid
System	dynamic
Carrier frequency range	672.000-691.975 MHz
Transmitting power	25 mW/2.5 mW
Power supply	2 x 1.5 V batt. AA size
Operating time	> 8 h
Audio frequency range	30-18,000 Hz
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 51 mm x 265 mm
Weight	312 g
Packing dimensions (W x H x L)	0.075 x 0.06 x 0.295 m
Gross weight	0.461 kg
Net weight	0.323 kg