



TXS-606LT/2

Order No.: 1000186

PRODUCTINFOS

Multifrequency tie clip microphone transmitter,

with UHF PLL technology.

- 800 selectable UHF frequencies (672.000-691.975 MHz), can be synchronised with receivers TXS-606, TXS-626, TXS-646 or TXS-686 via ACT function
- Continuously adjustable sensitivity
- LCD for indicating group/channel, audio level and battery status
- Tie clip microphone with latchable 3.5 mm plug
- Belt clip
- Power supply via 2 x 1.5 V battery AA size (not supplied)

There are restrictions or requirements within the EU!

Please read the information regarding wireless systems in the section “IMPORTANT INFORMATION”!

SOUNDCHECK 04/2012

“The TXS-646 can receive four wireless channels at the same time - the hand-held transmitter provides a warm and powerful sound and stands its ground among the instruments ... the earband microphones allow for unobtrusive miking with both a low susceptibility to acoustic feedback and an excellent speech intelligibility ... the quad wireless system from IMG Stage Line provides a reliable operation at all times, is easy to use and impresses by a crisp sound.”

+ Clear sound

+ Very good price-performance ratio

+ Future-proof frequency range

(Test setup consisted of TXA-646 with TXS-606HT, TXS-606LT and HSE-70A/SK)

TECHNICAL SPECIFICATIONS

TXS-606LT/2

General information

Description	pocket transmitter
Carrier frequency range	672.000-691.975 MHz
Audio frequency range	30-18,000 Hz
Channels	1
Operating time	> 8 h
Admiss. ambient temp.	0-40 °C
Specifications transmitter	
Transmitting power	10 mW
Power supply transmitter	2 x 1.5 V batt. AA size
Width transmitter	61 mm
Height transmitter	106 mm
Depth transmitter	27 mm
Weight transmitter	96 g
Connections transmitter	1 x 3.5 mm jack