



TXS-707HSE

Order No.: 0257550

PRODUCTINFOS

Multifrequency pocket transmitter,

with UHF PLL technology.

- 100 selectable UHF frequencies (667.000-691.750 MHz), can be synchronised with receiver TXS-727 or TXS-707 via SYNC function
- Continuously adjustable sensitivity
- Gain control
- Mute function
- LCD for indicating channel and battery status
- Suitable for combination with headband/earband microphones and tie clip microphones with 3-pole mini XLR connector
- Belt clip
- Operating range: 90 m (free field)
- Power supply via 2 x 1.5 V battery AA size (not supplied)

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

FAQ

How many wireless systems TXS-70... can be operated simultaneously?

With optimum local conditions, it is possible to operate 11 wireless systems TXS-707, TXS-707HSE and TXS-707LT simultaneously.

TECHNICAL SPECIFICATIONS

TXS-707HSE

General information

Description	pocket transmitter
Carrier frequency range	667.000-691.750 MHz
Audio frequency range	30-18,000 Hz
Channels	1
Operating time	> 15 h
Admiss. ambient temp.	0-40 °C
Specifications transmitter	
Transmitting power	10 mW
Power supply transmitter	2 x 1.5 V batt. AA size
Width transmitter	62 mm
Height transmitter	105 mm
Depth transmitter	26 mm
Weight transmitter	77 g
Connections transmitter	1 x 3-pole mini XLR