



TXS-707LT

Order No.: 0257570

PRODUCTINFOS

Multifrequency tie clip microphone transmitter,

with UHF PLL technology.

- 100 selectable UHF frequencies (667.000-691.750 MHz), can be synchronised with receiver TXS-727 or TXS-707 due to SYNC function
- Continuously adjustable sensitivity
- Gain control
- Mute function
- LCD for indicating channel and battery status
- Tie clip microphone with latchable 3.5 mm plug
- Belt clip
- Operating range: 90 m (free field)
- Power supply via 2 x 1.5 V battery AA size (not supplied)

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

How many wireless systems TXS-70... can be operated simultaneously?

With optimum local conditions, it is possible to operate 11 wireless systems TXS-707, TXS-707HSE and TXS-707LT simultaneously.

TECHNICAL SPECIFICATIONS

TXS-707LT

General information

Description	pocket transmitter
Carrier frequency range	667.000-691.750 MHz
Audio frequency range	30-18,000 Hz
Channels	1
Operating time	> 15 h
Admiss. ambient temp.	0-40 °C
Specifications transmitter	
Transmitting power	10 mW
Power supply transmitter	2 x 1.5 V batt. AA size
Width transmitter	62 mm
Height transmitter	105 mm
Depth transmitter	26 mm
Weight transmitter	77 g
Connections transmitter	1 x 3.5 mm jack