



TXS-812SET

Order No.: 0252600

PRODUCTINFOS

Wireless 2-channel microphone system

- 2 microphone transmitters, 1 receiver, 1 plug-in power supply
- Two-channel UHF version (non-diversity) with channel mixing function which can additionally be selected
- Volume and squelch controls for each channel
- Each channel with LEDs for indicating RF signal and audio signal

Licence-free in the EU.

TECHNICAL SPECIFICATIONS

TXS-812SET

General information

Description	wireless microphone system
Carrier frequency range	863.80 MHz , 864.20 MHz
Audio frequency range	40-15,000 Hz

TXS-812SET

Channels	2
THD	< 0.5%
Dynamic range	> 90 dB
RF S/N ratio	> 80 dB
Admiss. ambient temp.	0-40 °C
Specifications transmitter	
Transmitting power	< 10 mW
Operating range	approx. 30 m
Power supply transmitter	2 x 1.5 V batt. AA size (not supplied)
Width transmitter	52 mm
Height transmitter	52 mm
Depth transmitter	260 mm
Weight transmitter	240 g
Specifications receiver	
Audio signal receiver	0-200 mV/10 kΩ (jack) 0-400 mV/10 kΩ (XLR, bal.)
Power supply receiver	via encl. plug-in power supply
Width receiver	210 mm
Height receiver	46 mm
Depth receiver	190 mm
Weight receiver	560 g
Connections receiver	2 x XLR, bal. 1 x 6.3 mm jack, unbal.