



ULM-164/SW

Order No.: 0202240

PRODUCTINFOS

Universal line mixer,

6 channels.

- 6 stereo inputs/mono inputs
- 2 stereo outputs, independent of each other (master 1 via RCA and 6.3 mm jack), 1 mono output
- 3-way equalizer
- LED VU meter, switchable for both outputs
- Clip LED for each channel
- Balance controls with centre click for the stereo input channels
- Extended muting function
- Adjustable headphone output
- 482 mm (19") rack installation, 1 RU

TECHNICAL SPECIFICATIONS

ULM-164/SW

No. of channels	6
No. of inputs	12
Line input	150 mV/50 k Ω (stereo), 6 x RCA L/R 150 mV/25 k Ω (mono), 6 x 6.3 mm jack, unbal.
Master output	1 V/600 Ω (stereo), 2 x RCA (1 x 6.3 mm) L/R 2 V/600 Ω (mono), 1 x 6.3 mm jack
Headphones	$\geq 8 \Omega$, 1 x 6.3 mm jack
Frequency range	20-20,000 Hz

ULM-164/SW

THD	0.05%
S/N ratio	69 dB, unweighted
Equalizer bass	± 12 dB/80 Hz
Equalizer midrange	± 12 dB/1 kHz
Equalizer treble	± 12 dB/10 kHz
Power supply	~ 230 V/50 Hz/10 VA
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	10 VA
Admiss. ambient temp.	0-40 °C
Dimensions	482 x 48 x 175 mm, 1 RS
Width	482 mm
Height	48 mm
Depth	175 mm
Rack units, RU	1
Weight	2.3 kg
Packing dimensions (W x H x L)	0.18 x 0.047 x 0.482 m
Gross weight	3.035 kg
Net weight	2.32 kg