



MPX-205/SW

Order No.: 0202190

Price upon request

PRODUCTINFOS

Stereo DJ mixer

- 1 DJ mic, 4 stereo channels, switchable line/phono (1+2) and line/line (3+4)
- Stereo effect send/return
- 2 master outputs
- Automatic talkover and on-air switch for DJ mic
- LED level display, can be switched between the two master outputs and PFL
- 3-way equalizer with cut function for stereo channels
- 2-way tone control for DJ mic
- Gain control for each input
- Pre-fader listening (PFL) to the stereo inputs and outputs via adjustable headphone output
- Crossfader with assignment switches
- Connection for gooseneck light GNL-404

TECHNICAL SPECIFICATIONS

MPX-205/SW

No. of channels	5
No. of inputs	10
Mic input	1.5 mV, 1 x 6.3 mm jack
Line input	150 mV, 3 x RCA L/R
CD input	150 mV, 3 x RCA L/R
Phono input	3 mV, 2 x RCA L/R
Effect return	135 mV, 1 x RCA L/R
Master output	1 V/600 Ω , 1 x 3-pole XLR L/R
Record output	330 mV/600 Ω , 1 x RCA L/R
Monitor output	300 mV/600 Ω , 1 x RCA L/R
Effect send	1.2 V/600 Ω , 1 x RCA L/R
Headphones	$\geq 8 \Omega$, 1 x 6.3 mm jack
Gooseneck lamp	12 V/5 W, 1 x 4-pole XLR
Frequency range	20-20,000 Hz
THD	0.05%
S/N ratio	> 50 dB
Equalizer bass	+15 dB, -30 dB/50 Hz
Equalizer midrange	+15 dB, -30 dB/1 kHz
Equalizer treble	+15 dB, -30 dB/10 kHz
Talkover	-12 dB, automatic
Crossfader	yes
Power supply	~ 230 V/50 Hz/14 VA
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	14 VA
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	222 mm
Depth	110 mm
Rack spaces, RS	5
Weight	4.3 kg