



## MX-1IO

Order No.: 0203160

**Price upon request**

### PRODUCTINFOS

#### 1-channel USB recording interface

- Integrated USB audio interface (will be identified and addressed as an external sound card)
- Full-duplex USB port (allows for simultaneous recording and reproduction) for reproduction of digital audio data from a PC and for recording mixings onto a PC
- 1 mono input channel with XLR input (mic) and 6.3 mm input (switchable mic/line)
- Selectable 20 dB attenuation and LED level display
- 1 additional stereo input
- 1 x 6.3 mm jack output L/R
- 1 x 3.5 mm stereo jack output
- Adjustable headphone output
- +48 V phantom power, can be activated as required
- Stereo LED level display
- Robust metal housing of compact size

## TECHNICAL SPECIFICATIONS

### MX-110

No. of channels	1
No. of inputs	3
Mic input	2.5 mV, 1 x 3-pole XLR
Line input	45 mV, 1 x 6.3 mm jack 11 k $\Omega$ (line)/460 k $\Omega$ (inst.)
Aux input	1.25 V, 1 x 3.5 mm jack
Master output	500 mV, 1 x 6.3 mm jack L/R
Aux output	500 mV, 1 x 3.5 mm jack
Headphones	$\geq 16 \Omega$ , 1 x 3.5 mm jack
USB	yes
Frequency range	20-20,000 Hz
THD	$\leq 0.03\%$
Crosstalk	92 dB
Phantom power	+48 V
Power supply	via USB interface DC 5 V/500 mA
Operating voltage (possible alternative)	DC 5 V
Power supply (possible alternative)	500 mA
Admiss. ambient temp.	0-40 °C
Width	120 mm
Height	50 mm
Depth	110 mm
Weight	498 g