



DELTA-160

Order No.: 0203190

PRODUCTINFOS

Digital or analogue? Zeros and ones or analogue faders? Why not both?

The new digital mixer DELTA-160 combines the best of both worlds: full convenience and flexibility of a digital mixer with the intuitive operation of a standard analogue mixer. No matter whether on stage, in the rehearsal room or in a small basement club, the DELTA-160 is the first choice for live mixers, DJs and bands who value an outstanding sound, maximum functionality and reliable technology, but really want to concentrate on one thing only: the music.

16 channels, 9 motorised faders, digital gains, a large touch screen and a robust metal housing stand for performance and versatility which are normally not found in this price class. Key functions can be controlled via haptic faders. The convenient touch display and clearly arranged user interface add the final touch to your mix. Thus, you always have your sound under control, even remotely via iOS.

16-channel digital audio mixer

- 12 mono input channels (comb. inputs XLR/6.3 mm jack)
- 2 stereo input channels
- 1 S/PDIF input
- 1 USB audio channel
- USB recording (stereo master) and playback with 192 kHz/24 bits max.
- Integrated DSP (2 x reverb, 2 x modulation, 2 x delay, 2 x 31-band graphic equalizer)

- 8 XLR outputs
- 1 monitor output (6.3 mm jack)
- 1 AES/EBU output
- 1 S/PDIF output
- Can be remote-controlled via app (iOS)
- +48 V phantom power, can be activated as required for each mono input channel
- 1 adjustable headphone output
- 17.8 cm (7") colour LCD touch screen for display and settings
- Supplied with power supply

TECHNICAL SPECIFICATIONS

DELTA-160

| | |
|-----------------------|--------------------------------|
| No. of channels | 16 |
| No. of inputs | 20 |
| Mic input | 0.4 mV/3 mV, bal. (comb. jack) |
| Line input | 8 mV, bal. (stereo) |
| Master output | 700 mV, bal. (XLR) |
| Monitor output | 700 mV, bal. (6.3 mm jack) |
| Headphones | > 8 Ω |
| WiFi | yes, via USB Wi-Fi Dongle |
| USB | yes |
| Frequency range | 20-20,000 Hz |
| THD | < 0.01% |
| Crosstalk | > 69 dB |
| Equalizer bass | DSP (4-band equalizer) |
| Equalizer midrange | DSP (4-band equalizer) |
| Equalizer treble | DSP (4-band equalizer) |
| equalizer | DSP (15-band equalizer) |
| Phantom power | +48 V |
| Power supply | via encl. power supply |
| Admiss. ambient temp. | 0-40 °C |
| Width | 335 mm |
| Height | 140 mm |
| Depth | 410 mm |
| Weight | 5.55 kg |