



MPA-202

Order No.: 0320710

PRODUCTINFOS

2-channel low-noise microphone preamplifier

- 2 microphone inputs, XLR, bal.
- Gain control, 11 steps, 20-70 dB
- 2 level controls ± 5 dB
- LED green/red for indicating operation/peak
- Phantom power +12 V, can be activated as required
- Microphone phase, switchable for each channel
- Low cut: 15-240 Hz, continuously adjustable
- Subsonic filter 15 Hz, 18 dB/oct.
- 2 line outputs, XLR bal.
- 2 line outputs, RCA unbal.

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.

Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

TECHNICAL SPECIFICATIONS

MPA-202

Description	microphone preamplifier
Frequency range	20-20,000 Hz
Input sensitivity	0.16-150 mV switchable
Input impedance	4.4 k Ω (bal.) 2.2 k Ω (unbal.)
Output signal	1-14 V (line, bal.) 1-7 V (line, stereo)
Output impedance	100 Ω /600 Ω
Gain	15-75 dB
Crossover frequency	15-240 Hz, 6 dB/oct. (low cut), 15 Hz, 18 dB/oct. (subsonic)
Low cut	100 Hz
S/N ratio	> 68 dB, unweighted > 87 dB, weighted
THD	< 0.01%
Admiss. ambient temp.	0-40 °C
Power supply	via encl. plug-in power supply
Dimensions	116 x 55 x 135 mm
Weight	980 g
Inputs	2 x XLR 2 x XLR
Outputs	2 x RCA

MPA-202

EAN code

4007754185461

Net weight

0.897 kg