



STA-235

Order No.: 0253210

PRODUCTINFOS

Stereo PA amplifier,

with integrated limiter.

- LCD for indicating temperature, operating mode, power
- 2 operating modes can be selected (stereo or bridged)
- Limiter function can be activated as required
- Temperature-controlled fans
- 2 level controls
- Ground lift function
- Speaker switch-on delay
- Protective circuit with LED indication for protection against short circuit and overheating
- Each channel with LEDs for indicating overload, level and signal

TECHNICAL SPECIFICATIONS

STA-235

Peak output power	1,400 W
Power rating	1,000 W
Power rating at 4 Ω	2 x 500 W
Power rating at 8 Ω	2 x 400 W
Power rating with 8 Ω bridged operation	1 x 1,000 W

STA-235

Channels	2
Inputs	1.2 V/10 kΩ
Frequency range	10-50,000 Hz
Integrated limiter	yes
S/N ratio	> 80 dB
Crosstalk attenuation	> 50 dB
THD	< 0.1%
Power supply	~ 230 V/50 Hz/2,000 VA
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	2,000 Hz
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	100 mm
Depth	330 mm
Rack units, RU	2
Weight	11.5 kg
Connections	1 x 3-pole XLR L/R, bal.
	1 x 6.3 mm jack L/R, bal.
	3 x SPEAKER
	2 x pair of screw terminals
Packing dimensions (W x H x L)	0.37 x 0.14 x 0.51 m
Gross weight	13.52 kg
Net weight	12.6 kg