



STA-500

Order No.: 0243970

PRODUCTINFOS

Stereo PA amplifier,

for general applications.

- Fan cooling
- 2 level controls
- Ground lift switch
- Speaker switch-on delay
- Protective circuit with LED indication for protection against short circuit, overheating and DC voltage overlay at the outputs
- 1 LED per channel for indicating overload (clip)

TECHNICAL SPECIFICATIONS

STA-500

Peak output power	600 W
Power rating	400 W
Power rating at 4 Ω	2 x 200 W
Power rating at 8 Ω	2 x 125 W
Channels	2
Inputs	1.3 V/55 k Ω
Frequency range	10-20,000 Hz

STA-500

Integrated limiter	no
S/N ratio	64 dB
Crosstalk attenuation	> 55 dB
THD	< 0.05%
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	730 VA
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	95 mm
Depth	300 mm
Rack units, RU	2
Weight	6.6 kg
Connections	1 x 6.3 mm jack L/R 1 x RCA L/R 2 x SPEAKER 1 x 6.3 mm jack L/R 2 x pair of screw terminals
Packing dimensions (W x H x L)	0.37 x 0.14 x 0.51 m
Gross weight	7.45 kg
Net weight	6.64 kg