



STA-500

Order No.: 0243970

PRODUCTINFOS

Stereo PA amplifier,

for general applications.

- Fan cooling
- 2 level controls
- Ground lift switch
- Speaker switch-on delay
- Protective circuit with LED indication for protection against short circuit, overheating and DC voltage overlay at the outputs
- 1 LED per channel for indicating overload (clip)

TECHNICAL SPECIFICATIONS

STA-500

| | |
|---------------------|--------------|
| Peak output power | 600 W |
| Power rating | 400 W |
| Power rating at 4 Ω | 2 x 200 W |
| Power rating at 8 Ω | 2 x 125 W |
| Channels | 2 |
| Inputs | 1.3 V/55 kΩ |
| Frequency range | 10-20,000 Hz |

STA-500

| | |
|--------------------------------|---|
| Integrated limiter | no |
| S/N ratio | 64 dB |
| Crosstalk attenuation | > 55 dB |
| THD | < 0.05% |
| Mains voltage | ~ 230 V |
| Mains frequency | 50 Hz |
| Power consumption, operation | 730 VA |
| Admiss. ambient temp. | 0-40 °C |
| Width | 482 mm |
| Height | 95 mm |
| Depth | 300 mm |
| Rack spaces, RS | 2 |
| Weight | 6.6 kg |
| Connections | 1 x 6.3 mm jack L/R 1 x RCA L/R 2 x SPEAKER 1 x 6.3 mm jack L/R 2 x pair of screw terminals |
| Packing dimensions (W x H x L) | 0.37 x 0.14 x 0.51 m |
| Gross weight | 7.45 kg |
| Net weight | 6.64 kg |