



## STA-300D

Order No.: 0257330

### PRODUCTINFOS

#### Stereo class D PA amplifier

- 2 operating modes can be selected (stereo or bridged)
- Limiter function can be activated as required
- 2 level controls
- Temperature-controlled fan
- Protective circuit with LED indication for protection against short circuit, overheating and DC voltage overlay at the outputs
- Each channel with LEDs for indicating overload (clip) and signal

### TECHNICAL SPECIFICATIONS

#### STA-300D

Peak output power	350 W
Power rating	300 W
Power rating at 4 $\Omega$	2 x 150 W
Power rating at 8 $\Omega$	2 x 100 W
Power rating with 8 $\Omega$ bridged operation	1 x 300 W
Channels	2
Inputs	1 V/12 k $\Omega$
Frequency range	20-20,000 Hz
Integrated limiter	yes
S/N ratio	> 96 dB
Crosstalk attenuation	> 70 dB
THD	< 0.05%

**STA-300D**

Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	510 VA
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	52 mm
Depth	290 mm
Rack spaces, RS	1
Weight	3.7 kg
Connections	1 x 3-pole XLR L/R 1 x 6.3 mm jack L/R 1 x SPEAKER L/R
Packing dimensions (W x H x L)	0.38 x 0.12 x 0.55 m
Gross weight	4.75 kg
Net weight	3.84 kg